


AC series

空气过滤器组合(两联件)
F.R.L Combination



规格/Specification

符号/Symbol

保证耐压力/Ensured Pressure Resistance	1.5MPa(15kgf/cm ²)
最高使用压力/Highest Working Pressure	1.0MPa(10kgf/cm ²)
环境及流体温度/Ambient and Fluid Temperature	5~60℃
*过滤精度/*Filter Precision	25 um
建议用油/Recommended Oil Use	透平1号油/Turbine NO.1 Oil ISOVG32
容器材料/Container Material	聚碳酸酯/Polycarbonate
防护罩/Protective Cover	有/Available
调压范围/Pressure Regulating Range	0.05~0.85MPa(0.5~8.5kgf/cm ²)
阀型/Valve Type	带溢流型/With Overflow

还有5、50μm可供选择。/*5、50μm available in addition

型号 Model	规格 /Specifications					配件/Accessories		
	组件/Assembly		*额定流量 /Rated Flow (L/min)	*接管口径 /Port Size (G)	压力表口径 /Pressure Gauge Size	重量 /Weight (kg)	托架 /Bracket	压力表 /PressureGauge
	过滤器 /Filter	油雾器 /Mist Separator						
EAC2010-01	EAW2000	EAL2000	500	1/8	1/8	0.66	Y20T	G36-10-01
EAC2010-02				1/4				
EAC3010-02	EAW3000	EAL3000	1700	1/4	1/8	0.98	Y30T	
EAC3010-03				3/8				
EAC4010-03	EAW4000	EAL4000	3000	1/8	1/4	1.93	Y40T	G46-10-02
EAC4010-04				1/2				
EAC4010-06	EAW4000-06	EAL4000-06	3000	3/4	1/4	1.99	Y50T	
EAC5010-06	EAW5000	EAL5000	4000	3/4	1/4	3.20	Y60T	
EAC5010-10				1				

*供应压力为0.7MPa(7.1kgf/cm²)设定压力为0.5MPa(5.1kgf/cm²)的情况下

*Under the circumstance that the supply pressure is 0.7MPa(7.1kgf/cm²)and set pressure is 0.5MPa(5.1kgf/cm²)

**接管口径另有Rc、NPT螺纹可供选择:

Rc.and NPT port size are available

